



Jiangyin Aupu machinery Co., LTD.

| | | | | | | | |
|--|--|------|-----|---------------------------|--|--------------------|------|
| Address: No.11 Yanshan Road Changshou Village Zhouzhuang Town Jiangyin City Jiangsu China | | | | Fax: +86-510-86961108 | | | |
| Sales calls: +86-510-86961170,+86-13382283038 | | | | Zip:214424 | | | |
| Web: http://www.aupujx.com | | | | E-mail: wilson@aupujx.com | | | |
| Company | | | Fax | | | | |
| Tel | | | | | | | |
| Addressee | | Page | 5 | Addresser | | Mr.Wilson Zhang | Date |

Quotation and Specifications

1.Photos





SGS



TÜVRheinland
Precisely Right.



2. Technical parameter

| | | |
|----------------------------------|---------------------------|--------|
| Type | Y81F-160 | |
| The packet method | turn | |
| The nominal thrust | The pressure cylinder | 1600KN |
| | Lateral pressure cylinder | 1250KN |
| | Door cover oil cylinder | 800KN |
| | The packet cylinder | 630KN |
| Stroke | The pressure cylinder | 600mm |
| | Lateral pressure cylinder | 1050mm |
| | Door cover oil cylinder | 1250mm |
| | The packet cylinder | 300mm |
| Compression chamber size (L×W×H) | 1400*900*700mm | |
| Packet block size (L×W×H) | 350*350*400-1200 | |
| The production efficiency | 1800-2200(KG/H) | |
| The system pressure | 25Mpa | |
| Pump | 160YCY14-1B | |
| A single cycle time | ≤90s | |
| Voltage | 380V, 50Hz | |
| Power | 22KW | |
| The motor speed (r/min) | 980 | |
| Pump discharge (ml/r) | 160 | |
| Tank capacity (L) | 700 | |
| Size of machine(mm) | 4600X2500X2000 | |
| Weight of machine | 8 tons | |
| Delivery time | Inventory or 15 days | |
| Quotation have deadline | 30 days | |
| Price | USD14,200 | |

| | | | |
|----------------------------------|---------------------------|-------------------------|-------------------------|
| TYPE | | Y81F-160B | Y81-160A |
| The packet method | | turn | turn |
| The nominal thrust | The pressure cylinder | 1600KN | 1600KN |
| | Lateral pressure cylinder | 1250KN | 1250KN |
| | Door cover oil cylinder | 630KN | 630KN |
| | The packet cylinder | 630KN | 630KN |
| Stroke | The pressure cylinder | 650mm | 750MM |
| | Lateral pressure cylinder | 1000mm | 1200MM |
| | Door cover oil cylinder | 1100mm | 1150MM |
| | The packet cylinder | 365mm | 365MM |
| Compression chamber size (L×W×H) | | 1600*1200*800mm | 1600*1000*800MM |
| Packet block size (L×W×H) | | 400*400MM | 400X400 |
| Block density | | ≥1800 kg/m ³ | ≥1800 kg/m ³ |
| The production efficiency | | 2500-4000KG/H | 2000-3500KG/H |
| The system pressure | | 25Mpa | |
| Pump | | 63YCY14-1B*2 | 160YCY14-1B |
| Pump discharge | | 63ml/r | 160ml/r |
| A single cycle time | | ≤120s | ≤110s |
| Voltage | | 380V, 50Hz | |
| Power | | 30KW | 22KW |
| The motor speed (r/min) | | 970 | |
| Pump discharge (ml/r) | | 63*2 | 160 |
| Tank capacity (L) | | 1400 | 1200 |
| Size of machine(mm) | | 4500X3000X2600 | 4300x3000x2600 |
| Weight of machine | | 12tons | 10.5tons |
| Manner of packing | | nude packing | |
| Delivery time | | 30 days | 30 days |
| Quotation have deadline | | 30 days | |
| Price | | USD23470 | USD19100 |

3.Configuration :

- A. Electrical: French schneider
- B. Oil Pump: Qidong High pressure oil pump
- C. Oil cylinder seals: Germany USK
- D. Oil pipe seals: Germany FOLON.A
- E. Pressure gauge: USA Joseph KK
- F. High pressure hose: Pikes
- G. Travel switch: French Schneider
- H. The tubing connector: USA EATON

4. Note

A.This price for FOB SHANGHAI based.

B.Delivery time: Inventory or 20 days

C.Validity date:30 days

D. Guarantee for quality:12 months

E. Payment : 30% advance, 70% paid before shipment, T/T .

F. The product has passed ISO9001-2000 international quality system certification and European Union CE certification!

G. Color: Customer defined!

Contact: Mr Wilson Zhang

website: www.aupujx.com

email: wilson@aupujx.com

Skype: wilsonzzh

QQ:983365051

Mob:+86-13382283038

Tel:+86-510-86961170